



Removable Ribbon Cassette Unit Intermittent Thermal Printer

A simple ribbon cassette with high resolution 300 dpi thermal head. High print speed 333mm/sec. It offers reliable printing with high quality.

Simple Ribbon Cassette Unit

Ribbon can be changed in seconds reducing factory down-time.

Long Stroke Type THP301L

Two stroke print lengths are available. Standard print length of 29mm and long stroke length of 51mm.



SPECIFICATION

Model	THP301 / THP301L
Type	Intermittent Thermal Printer
Print Resolution	300dpi (12dots/mm)
Print Speed	333mm/sec, 9 steps variable
Print Area	53mm (W) x 29mm (L) / 53mm (W) x 51mm (L)
Thermal Ribbon	400m/roll (Max.)
Power Supply	AC100V/200V, 410VA, 50Hz/60Hz
Configuration	Main Body · Power Supply BOX · EUI2
Weight (Main Body)	7.0kg
Dimensions (mm)	190 (W) - 183 (H) - 252 (D) (THP301) 210 (W) - 183 (H) - 252 (D) (THP301L)
Operating Environment	Temperature : 5°C - 40°C Humidity : Under 90%RH (no dew condensation)



5-2,3-Chome Itabashi, Itabashi-ku, Tokyo, Japan
TEL : +81-3-3964-4852 FAX : +81-3-3962-1277
URL : <https://www.edm-net.co.jp/>

Intermittent Thermal Printer

THP301

Agency